## abetap







## Features

reatures	
Maximum resolution	2048×1536
Viewing angle	Diagonal 156°, horizontal 114°, vertical 82°
Aspect ratio	4:3
Color night vision	Support
Intelligent function	Human shape detection, vehicle detection, package detection, pet capture, activity area
Battery capacity	5200 mAh
Usage time	6-8 months(under the condition of recording 20 10s videos per day)
Alarm method	Mobile APP alarm push, alarm sound warning and equipment white light flashing (optional)
Record method	Alarm triggered, manual recording
Protections	Concealed disassembly method, anti-theft alert
Compatibility	Mechanical chime, Alexa and Google Home supported
Video storage	Cloud storage, local micro SD card (up to 128 GB), mobile memory
Protection grade	IP65
Bracket specification	1/4 universal screw hole
Certificate	CE, FCC, RoHS, WEEE, MSDS, UN38.3



## abetap

Spe	cifications	

	•	
	Sensor	1/2.8" CMOS
	Focal Length	2.8 mm
Camera	Optical Field of View	156° diagonal, 114° horizontal, 82° vertical
	Minimum Illumination	0.01 lux
Audio	Input	Built-in microphone
	Output	Built-in speaker
	Two-way Audio	Full duplex
	Audio Compressing	AAC
Video	Video Compressing	H.264, H.265
	Lighting Frequency	50 Hz, 60 Hz
	Frame Rate	15 fps
	Maximum Resolution	2048 × 1536
	Light Source for Night Vision	Infrared LED
	Wireless Standard	Wi-Fi: 2.4 GHz (IEEE 802.11 b/g/n) FSK: 915 MHz, 868 MHz, 433 MHz
Network	Protocols Supported	TCP/IP, UDP/IP, DHCP, RTMP, MUTP, FSK
	IP Address Type	Dynamic IP address
Recording	Recording Method	Alarm triggered recording, and manual recording
	Video Storage	Cloud storage, local Micro SD card (up to 128 GB), and mob phone memory
	AI Function	Human detection, vehicle detection, pet detection, package detection, activitiy zone
	Wake-up Method	PIR body induction wake-up, remote wake-up and button wa
Function	Alarm Notification	Alarm push by mobile app, indicator light flashing and alarm sound warning
	Indicator	RGBY four-color LED
	Mechanical chime and smart speaker compatibility	Mechanical chime, Alexa and Google Home supported
	Capacity	5200 mAh or 6700 mAh optional
	Removability	Unremovable
	Working Time	5 months (recording 20 pieces of 10-second video per day)
Battery	Standby Time	1 year
	Charging Voltage	
	Charging Time	10 hours (DC)
	Protection	Over-charge, over-discharge, over-current, short circuit and charging protection at high and low temperature
Power Consumption	Standby	3 mW
	Daytime Working	1 W
	Nighttime Working	2.5 W
Interface	Power	Micro USB
	Storage	Micro SD card
	Кеу	Power key, doorbell key and reset key
Installation	Installation Method	Bracket installation
	Bracket Type	Standard: flat bracket
Tamper-proof	Mechanical method	Optional: left and right tilt brackets, up and down tilt brackets Tools required for doorbell removal
	Electronic method	Alarm sound warning and mobile phone notification in case of
Environment	Dustproof and Waterproof	illegal doorbell removal (optional) IP65
	Operating Temperature	-10 ~ 45
	Storage Temperature	-20 ~ 60
	Storage Temperature Dimension	-20 ~ 60 144 mm × 46 mm × 31 mm (without bracket)
Prodoct Dimension		
	Dimension	144 mm × 46 mm × 31 mm (without bracket)

