

# DH-PFM320-010US

## 12V 1A Power Adapter



### Features

- CCTV Power supply ,100—240 VAC to 12 VDC 1A;  
Wall plug, easy to use.
- Overvoltage, overcurrent, and short circuit protection.  
Good quality,
- stable performance, V0 level flame resistance.

### Technical Specifications

Model	DH-PFM320-010US
Key Parameters	
Input voltage	100 VAC-240 VAC, 50/60Hz, 0.4A
Output voltage	12 VDC
Output current	1 A
No-Load power consumption	≤0.3 W
Working temperature	0 °C to 40 °C (32 °F to 104 °F)
Transformation Efficiency	≥77.76%
Appearance	
Dimensions	60.6mm×29.00mm×40.0mm (2.36" × 1.14" × 1.57")
Input	Plug with American standard
Output	Φ5.5 mm×Φ2.1 mm×10 mm (Φ0.22" × Φ0.08" × 0.39")
Color	Black
Safety Standards	
Certification	CE, FCC , UL - VI

### Important Safeguards and Warnings

- Please read this manual carefully before using the product.
- The use must conform to local electrical safety regulations.
- The size of the DC interface on the product output cable should match the size of the terminal product interface.
- Before powering on, make sure that the powering voltage conforms to the product input voltage.
- When connecting the product with the terminal product, do not operate with power. During wiring, the input and output specifications and parameters need to meet the product requirements.
- To reduce the risk of fire or electric shock, do not expose the product to rain or moisture.
- If the product does not work properly, contact the store where you purchased the product or the nearest service center.

Do not disassemble or dismantle the device without a professional present. (The company is not responsible for damages to the device or other product problems caused by excessive use or other improper use).

Dimensions (mm /inch )

