

X11



Twelve Function Configurations









Wireless Conn

Area Monitorina

Accurate Notification



Phone Monitoring

Features

- Easy to install and use
- Clear and smooth video browsing; intelligent transmission giving full play to capabilities of the network
- Online firmware upgrade, and synchronous updating of the functions and experience
- ◆ Two-way voice intercom supported; echo eliminated; noise suppressed
- Compatible with Android; remote real-time monitoring supported with the IOS intelligent terminal
- 2-megapixel high resolution (1920X1080) for clear picture quality
- Lighting for infrared night vision (with a night vision distance of 7m); 24h around-the-clock monitoring; IR-CUT switching; free of color cast in the daytime; clearer night vision
- Intelligent push to filter out useless information
- ◆ 2.4G Wi-Fi supported (IEEE802.11b/g/n)
- Intelligent storage algorithm, small space can accommodate more content, support Micro SD card, cloud storage
- QR code intelligent connection and network allocation supported
- Supporting human detection, activity zone, intelligent push and pet snapshot
- ◆Small and exquisite appearance, various colors
- Support one-key remote call, and can be extended to multiple call modes





Specifications

Master processor	SOC	ARM
Image Sensor	Sensor	1/3" color CMOS sensor
	Lens	M12, f: 4mm, F2.0, 3-megapixel
	Visual angle	H (horizontal) 63 degrees; V (vertical) 50 degrees; D (diagonal) 89 degrees
	Minimum illumination	0.01Lux
Audio	Input/Output	Two-way voice intercom available (built-in Microphone and speaker)
	Audio compression method	AAC
Video	Video compression method	H.264
	Lighting frequency	50Hz, 60Hz
	Image frame rate	15fps
	Maximum Image Resolution	1920*1080P
	Light Source for Night Vision	IRCUT double filter automatic switching, 6 infrared lamps (850nm wavelength), irradiation distance:10 meters
Network	Wireless Network	2.4G Wi-Fi (IEEE802.11b/g/n), built-in antenna
	Protocols Supported	TCP/IP, UDP/IP, DHCP, RTMP, MUTP
	IP Address Supported	Dynamic IP address supported
Alarm	Alarm detection	Motion Detection
	Alarm linkage	Support video recording, sound alarm
	Alarm notification	Alarm push by mobile APP
	Emergency assistance	Support one-key remote call
Al	Intelligent function	Intelligent push, pet snapshot, human detection, package detection, motion tracking
Pan tilt	Rotation angle	H (horizontal) 0° ~ 350°; V (vertical) -20° ~ 60°
Interfaces	Power Supply	1 Micro USB interface, DC 5V/1.5A
	SD card	1 Micro SD card (up to 128GB)
	Keys	1 function key
Other	Adjustable lens	Not adjustable
	LED indication	Monochrome white light (power/network signal/function indicator)
	Video storage method	Micro TF card (up to 128GB) local storage, cloud storage
	Install method	Ceiling or wall hanging
Environment	Dustproof and waterproof	no
	Operating environment	-10° ~ 45°C /10% ~ 80% (no condensation)
	Storage environment	-20°C ~ 60° /0% ~ 90% (no condensation)
Color	Appearance color	White
Specification	Dimensions (L*W*H)	85mm*85mm*112mm
	Net Weight	Approx. 186g
Certifications	Certificate	CE, FCC, RoHS
	•	







