

FSID22FF

21.5" FHD Monitor



Features:

- · Light and cost-effective plastic housing;
- · Ultra-narrow bezel , elegant appearance, plastic base;
- \cdot 178°H/178°V extra-wide viewing angle for overall viewing performance;
- · High fidelity digital processing for a brilliant and vivid video;
- · Support multiple signal inputs such as HDMI, VGA;
- · Physical button control mode;
- · Low energy consumption, long service life;
- · Anti-blue light design, eye-protective.















Technical Specification

Model		
Model	FSID22FF	
Display		
Screen Size	21.5"	
Panel type	VA	
Aspect Ratio	16:9	
Resolution	1920×1080 (FHD)	
Backlight	LED	
Brightness/Luminance	250 cd/ m² (max)	
Contrast	3000:1	
Display Color	16.7M(8bit)	
Color gamut Support	72% NTSC	
Viewing Angle(H/V)	178°(H)/178°(V)	
Refresh Rate	75Hz (max)	

Signals

Input	VGA×1, HDMI×1
Output	NO

General

Power Supply	DC 12V		
Consumption (Standard)	22W		
Consumption (Standby)	≤0.5W		
Net Weight	2.18kg (4.8lb)		
Gross Weight	3.4kg (7.5lb)		
Bezel Width	3.3mm(U/R/L) 15.2mm(B)		
Wall Mount	75x75 (3.0"x3.0")		
Dimension with stand (W×H×D)	492.7x284.0x48.4mm (20"x11.6"x1.9")		
Package(W×H×D)	598x99x366mm (24.4"x4.0"x14.9)		
Work Environment	Temperature	0℃~40℃ (32°F~104°F)	
work environment	Humidity	10%~85%	
Accessory			
Standard	HDMI cable, Adapter, base		
Certifications			

TBD

Rev 002.000

Certifications



Dimensions(mm)

